The Brinell BH3000 Hardness Tester is a sturdy, 3000 kgf (30 kN) hardness tester for the higher load Brinell scales (>187.5 kgf). Designed with a rugged construction to withstand the harshest environments, this reliable tester offers a high-rigidity and closed-loop load cell technology for accurate and safe load applications. Key features include a clamping device for securing parts to the exchangeable anvil, an easy-to-use user interface to set up and operate the tester, a built-in keypad calculator that accurately presents HB hardness values, and an LCD screen.

## Interface

- LCD screen that clearly displays results, statistics per test series, and language settings
- Integrated hardness calculator, hardness diagonals, value, statistics, and conversions

## **Load Selection**

• Load cell technology, means force accuracy and efficiency

# **Specimen Clamping**

• Heavy-duty clamping and protection device

### **Specimen Support**

• Various flat and V-anvils available, for most product geometries

# **Applications**

- Hardness from castings and forgings
- For flat and cylindrical work pieces
- Wide application within the automotive industry
- Heavy workshop testing
- Sample testing or quality
- control testing
- Various types of steels
- (Cast) Aluminum and other non-ferrous metals





#### BH3000

Down to 0.1in (3mm) diameter

100 - 240VAC, 60/50Hz External measuring microscope; mechanical 20x, 40x or 60x,

digital King Scan IV PC based measurement system

Hardness scales	НВ
Display	Hardness HB value (after entering diagonal length into key- pad calculator); Mean diagonal length; Test force; Dwell time; Ball diameter; Conversion; Limits
Hardness Resolution	0.1 unit if HB < 100; else 1.0 unit
Standards Compliant	ISO 6506, ASTM E10, JIS
Test Load Type	Load Cell Closed-Loop Control System
Test Cycle	Automatic
Test Loads	187.5, 250, 500, 750, 1000, 1500, 3000kgf
Brinell Scales	HBW 10/3000, HBW 10/1500, HBW 10/1000, HBW 10/500, HBW 10/250, HBW 10/100, HBW 5/750, HBW5/250, HBW 2.5/187.5
Indenters (optional)	Brinell Balls: 2.5, 5, 10mm
Load Duration	2 - 99 sec
	Vertical space 11in (280mm)
Specimen Accommodation	Horizontal space (from center-line) 5in (130 mm)
	External surfaces roughly grinded, Ra < 21.6 µm



Approx. Weight: 550 lbs [250kg]



Cylindrical Surfaces

Optics (optional)

Power



#### **Test Blocks and Indenters**

High quality Wilson® hardness standardized test blocks from Buehler® are calibrated in compliance with ASTM E384, ASTM E18, ASTM E10, ISO 6507, ISO 6508, or ISO 6506 where appropriate. Rockwell C standardized test blocks are directly NIST traceable. All calibrations and certifications are performed in an ISO/IEC 17025 compliant facility.



- Brinell indenters
- Hardness reference blocks with NVLAP, UKAS, or DKD certificate
- Various testing tables and XY-Stages
- Precision vices, V-blocks, and special clamps
- Clamping and protection attachment
- PC software databases for demanding applications
- Rugged floorstand with spindle hole

Inquire about additional Brinell accessories.

For a complete listing of consumables, please refer to our Product Catalogue or contact your local Buehler Sales Engineer. Buehler continuously makes product improvements; therefore technical specifications are subject to change without notice.



Mounting SimpliMet Grinding & Polishing EcoMet • AutoMet • MetaServ Imaging & Analysis OmniMet

# Hardness Testing Wilson®

BUEHLER
An ITW Company







BUEHLER Worldwide Headquarters 41 Waukegan Road Lake Bluff, Illinois 60044-1699 USA P: (847) 295-6500 www.buehler.com | info@buehler.com

BUEHLER Germany info.eu@buehler.com

**BUEHLER France** info.fr@buehler.com

BUEHLER United Kingdom info.uk@buehler.com

**BUEHLER Canada** info@buehler.ca

**BUEHLER Japan** info.japan@buehler.com

BUEHLER China china@buehler.com.hk

BUEHLER Asia-Pacific info@buehler.com.hk